

## **ACCESS® LED LIGHT INSTALLATION INSTRUCTIONS**

**NOTE:** Requires (3) AA batteries, not included in kit.

A. Open battery box with Phillips head screwdriver and install (3) AA batteries.

TIP: Change auto shutoff time while battery box is open.

B. Reattach box cover, do not overtighten screws.

**NOTE:** For best adhesion, air and surface temperature should be above 60°F for at least 2 hours before adhering the LED light.

- C. Clean area where LED light will be attached with soap and water or rubbing alcohol, wipe dry.
- D. Peel protective layer from adhesive strip and battery box to adhere
- E. Firmly press battery box and LED light strip to secure in place.



#### **WARNING:**

Cancer and Reproductive Harm www.P65Warnings.ca.gov



MADE IN CHINA 80312\_B

# **CHANGING AUTO SHUTOFF TIME**

**IMPORTANT:** To remove and reinstall terminal, use a tweezers. Ensure terminal is securely on pins.

### **AUTO SHUTOFF SWITCH SETTINGS:**

- Place terminal on top pins for 3 minutes (factory default)
- · Place terminal on middle pins for 5 minutes
- · Place terminal on bottom pins to disable auto shutoff

**NOTE:** If LED light turns off by timer, press on/off button twice to re-activate.

## ACCESSLEDLIGHT.COM

Reorder #80312





