

Recommended Air Filter Cleaning Intervals: 3000 Miles.

US Pat#US7,263,961B2

Part # 's Secret Weapon: 301-122 Application : 02-03 Acura TL - S / 2001-03 Acura CL-S 3.2L

Parts List : 1 x Weapon*R Intake pipe. /1 x Weapon*R Air Filter / 1 x 10mm x 36" Hose 2 x 3" Coupler / 1 x Intake System Bracket kit / 3 x 3" Clamp

- 1 Remove bolts securing OEM air cleaner box, loosen clamps on OEM rubber intake pipe.
- 2 Remove the coolant transfer / PCV hardline from from OEM intake and engine.
- 3 Mark the coolant tranfer hose origins, install the 10mm hose supplied in kit to those 2 locations.
- 4 Remove the OEM rubber intake tube, remove the OEM air cleaner box by pulling upwards.
- 5 Wipe the throttlebody clean of any grease or dirt, install the 3" coupler onto throttlebody, secure with OEM clamp.
- 6 Insert the intake pipe into 3" coupler on throttlebody, secure with supplied clamp.
- 7 Measure the OEM PVC hose, replace with supplied 10mm hose, install from PVC port to intake pipe.
- 8 Install the hoses from their point of origin and onto the Weapon *R intake pipe.
- ${\bf 9}$ Install the Weapon*R Hyper filter onto the end of the intake pipe.
- 10 Note: Dragon Filter Option : Disregard installation on Hyper filter.
 - Install 3" coupler onto Dragon or Secret Weapon air filter, secure with supplied clamp.
- 11 Install filter assembly onto the end of Weapon*R intake pipe, secure with OEM clamp.
- 12 Install U-shaped part of intake system bracket under the clamp on air filter.
- 13 Install the rubber mounting grommet to the closest hole to the Weapon*R air filter.
- 14 Bend the straight portion of the intake system bracket to the Rubber mounting grommet.
- 15 Secure with washer and nut included in bracket kit.
- 16 Position air intake pipe for clearance, making sure no parts are touching any part of the vehicle.
- 17 Check for hood clearance, re-adjust intake tube for perfect fitment and clearances.
- 18 Place Weapon*R CARB Sticker on a visible place in engine compartment. (If Applicable)

WARNING: EO# LABEL IS REQUIRED TO AID IN THE PASSING THE SMOG CHECK INSPECTION.

Note: Returned Products may be subject to a 25% restocking charge. **INSTALLED PRODUCTS ARE NON-REFUNDABLE !** Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from. Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.



Cold Airbox for CL and Adjustable Fuel Pressure regulator Kit available. If you have any Question about this Product, Please refer to our website @ WWW.WEAPON-R.COM Email your installed pictures of your WR product for a chance to receive a free gift. <u>Chris.wanstrath@weapon-r.com</u>