

Part # 's 959-111-102

Application: 2002 + ACURA RSX / 2003 + HONDA CIVIC SI

Parts List: 1 X ENGINE DAMPER / 1 X STRUT TOWER MOUNTING BRACKET

1 X L-BRACKET / 1 X MOUNTING HARDWARE KIT

- 1 Jack up the front of the vehicle, place jack stands under vehicle securely.
- 2 Place a piece of wood on top of the jack, slowly jack up the engine from the oilpan.
- 3 Raise up the jack till it is snug against the oilpan.
- 4 Remove the 2 bolts on the left side engine mount.
- 5 Install the L-Bracket onto the engine mount and tighten it back into place with OEM Nuts.
- 6 Install the engine damper kit on the L-bracket, secure with supplied mounting hardware.
- 7 Remove the two 12mm nuts on the Left side strut tower.
- 8 Install the Strut Tower Moutning Bracket onto the strut tower, tighten bracket with OEM 12mm Nuts.

NOTE: For Civic SI: Dril out the tow spots where the Strut tower mounting bracket goes and use two 12mm grade 8 bolts and nuts in place of the strut tower mounting bolts and nuts.

- 9 Install the other end of engine damper onto strut tower mounting bracket, secure with supplied hardware.
- 10 Adjust length of engine damper to desired length.
- 11 Lower jack from Oilpan slowly.
- 12 Jack up the front of the vehicle, remove jack stands and slowly lower vehicle.
- 13 Installation is complete.



Returned Products may be subject to a 25% restocking charge. INSTALLED PRODUCTS ARE NON-REFUNDABLE!

Report any defective or missing parts to the authorized Weapon*R dealer you purchased this product from.

Installation does require some mechanical skills. We recommend a qualified mechanic to install this product.

Other performance products available for this vehicle, for more details please check out our website at: